



Performance

Measuring range	3 to 6 %	6 to 24 %
Number of pump strokes	1(100 ml)	1/2(50 ml)
Correction factor	1/2	1
Sampling time	1 min	30 sec

 $\begin{array}{lll} \mbox{Detecting limit:} & 2 \% \ (1 \mbox{ pump stroke}) \\ \mbox{Colour change:} & \mbox{Black} \rightarrow \mbox{White} \\ \mbox{Corrections for temperature \& humidity:} \mbox{Unnecessary} \end{array}$

 $\label{eq:Relative standard deviation:} \qquad \qquad 5~\%~(for~6~to~24~\%)$

Shelf life: 3 years

Reaction principle

 $O_2 + 4TiCl_3 + 6H_2O \rightarrow 4TiO_2 + 12HCl_3$

Possible coexisting substances and their interferences

Substance	Concentration	Interference	Changes colour by itself to
Carbon dioxide	≧ 40%	+	} No
Carbon monoxide		No	J

Hydrogen chloride is trapped in the HCl filter layer.

Calibration gas generation

Dynamic gas dilution method

Special note

If more than 40% carbon dioxide is coexisted, the tube reading will be 1% higher than the true concentration. (At 21% oxygen concentration tube 31B indicates 22%)